

External Switching Power Supply Programme



Wall Plug adapters

S-1306 1~2.5 W

S-1196 2~6 W

S-1088 3~10 W

S-1298 3~24W

S-1183 30~60W



Desktop adapters

S-1318 5~30 W

S-1183 30~60W

S-1319 40~60 W

S-1223 75~90W

S-1250 120~130W

☞ **RoHS**

☞ **CE**

☞ **Short Lead time**

☞ **WEEE**

☞ **TUV/GS**

☞ **2 years warranty**



S-1306

Input Voltage Type: Universal Range
 AC Input Voltage: 90~264 Vac
 AC Input Frequency: 47~63 Hz
 AC Input Current: 0.1A RMS
 No. of Outputs: Single O/P
 Load Regulation: +/-5%
 Min. O/P Amper: 0A
 Operation Temperature: 0~40°C
 Protection: Short, Over Voltage, Over Current
 MTBF: 35 000 Hours
 Hold Up Time: 10 ms
 Safety: TUV/GS, CE, CB
 Environmental: RoHS, WEEE
 Weight: 60 grams
 Dimension: 49.3 mm (L), 32.6 mm (W), 21.2 mm (H)

PART NUMBER	POWER RATING [W]	O/P VOLTAGE [V]	MAX. O/P CURRENT [A]	Additional
S-1306-0103	1	3.3	0.30	
S-1306-0104	1	4.2	0.24	
S-1306-0105	1	5	0.2	
S-1306-0203	2	3.3	0.15	
S-1306-0204	2	4.2	0.5	
S-1306-0205	2	5	0.4	
S-1306-0305	2.5	5	0.50	

Product Code Rule

S	1306	03	05	W	2	E	1
S: switching L: linear D: DC/DC	Series	Watts	Output voltage	W: wall mount T: desktop B: open frame	Pin 2: 2 pins 3: 3 pins	E: European plug U: English plug -: USA plug	1: DC jack 5.5x2.1mm 2: DC jack 5.5x2.5mm 3: DC jack 3.5x1.35mm Other: call



S-1196

Input Voltage Type: Universal Range

AC Input Voltage: 90~264 Vac

AC Input Frequency: 47~63 Hz

AC Input Current: 0.3A RMS

No. of Outputs: Single O/P

Load Regulation: +/-5%

Min. O/P Amper: 0A

Operation Temperature: 0~40°C

Protection: Short, Over Voltage, Over Current

MTBF: 35 000 Hours

Hold Up Time: 10 ms

Safety: TUV/GS, CE, CB

Environmental: RoHS, WEEE

Weight: 90 grams

Dimension: 55 mm (L), 28 mm (W), 42 mm (H)

PART NUMBER	POWER RATING [W]	O/P VOLTAGE [V]	MAX. O/P CURRENT [A]	Additional
S-1196-0204	2	4.0	0.50	
S-1196-0204-1	2	4.2	0.48	
S-1196-0204-2	2	4.5	0.45	
S-1196-0205	2	5.0	0.40	
S-1196-0205-1	2	4.9	0.41	
S-1196-0212	2	12	0.17	
S-1196-0304	3	4.0	0.75	
S-1196-0304-1	3	4.2	0.71	
S-1196-0304-2	3	4.5	0.67	
S-1196-0205	3	5.0	0.60	
S-1196-0305-1	3	4.9	0.61	
S-1196-0312	3	12	0.25	
S-1196-0404	4	4.0	1.00	
S-1196-0404-1	4	4.2	0.95	
S-1196-0404-2	4	4.5	0.89	
S-1196-0405-1	4	4.9	0.82	
S-1196-0405-2	4	5.0	0.80	
S-1196-0412	4	12	0.33	
S-1196-0504	5	4.0	1.25	
S-1196-0504-1	5	4.2	1.19	
S-1196-0504-2	5	4.5	1.11	
S-1196-0505-1	5	4.9	1.02	
S-1196-0505-2	5	5.0	1.00	
S-1196-0512	5	12	0.42	

S-1196-0605-1	6	4.9	1.22	
S-1196-0605-2	6	5.0	1.20	
S-1196-0612	6	12	0.50	

Product Code Rule

S	1196	06	12	W	2	E	1
S: switching L: linear D: DC/DC	Series	Watts	Output voltage	W: wall mount T: desktop B: open frame	Pin 2: 2 pins 3: 3 pins	E: European plug U: English plug -: USA plug	1: DC jack 5.5x2.1mm 2: DC jack 5.5x2.5mm 3: DC jack 3.5x1.35mm Other: call



S-1088

Input Voltage Type: Universal Range
 AC Input Voltage: 90~264 Vac
 AC Input Frequency: 47~63 Hz
 AC Input Current: 0.5A RMS
 No. of Outputs: Single O/P
 Load Regulation: +/- 5%
 Min. O/P Amper: 0A
 Operation Temperature: 0~40°C
 Protection: Short, Over Voltage, Over Current
 MTBF: 35 000 Hours
 Hold Up Time: 10 ms
 Safety: GS/TUV, CB, CE
 Environmental: RoHS, WEEE
 Weight: 110 grams
 Dimension: 57 mm (L), 48 mm (W), 26 mm (H)

PART NUMBER	POWER RATING [W]	O/P VOLTAGE [V]	MAX. O/P CURRENT [A]	Additional
S- 1088-0303	3.3	3.3	1.00	
S- 1088-0312	3	12	0.25	
S- 1088-0315	3	15	0.20	
S- 1088-0503	5	3.3	1.50	
S- 1088-0505	5	5	1.00	
S- 1088-0605	6	5	1.20	
S- 1088-0606	6	6	1.00	
S- 1088-0609	6	9	0.67	
S- 1088-0610	6	10	0.60	
S- 1088-0612	6	12	0.50	
S- 1088-0615	6	15	0.40	
S- 1088-0805	7.5	5	1.50	
S- 1088-0806	8	6	1.33	
S- 1088-0808	7.5	7.5	1.00	
S- 1088-0909	9	9	1.00	
S- 1088-1010	10	10	1.00	
S- 1088-1012	9.6	12	0.80	
S- 1088-1015	9.5	15	0.63	

Product Code Rule

S	1088	10	15	W	2	E	1
S: switching L: linear D: DC/DC	Series	Watts	Output voltage	W: wall mount T: desktop B: open frame	Pin 2: 2 pins 3: 3 pins	E: European plug U: English plug -: USA plug	1: DC jack 5.5x2.1mm 2: DC jack 5.5x2.5mm 3: DC jack 3.5x1.35mm Other: call



S-1298

Input Voltage Type: Universal Range

AC Input Voltage: 90~264 Vac

AC Input Frequency: 47~63 Hz

AC Input Current: 0.5A RMS

No. of Outputs: Single O/P

Load Regulation: +/-5%

Min. O/P Amper: 0A

Operation Temperature: 0~40°C

Protection: Short, Over Voltage, Over Current

MTBF: 35 000 Hours

Hold Up Time: 10 ms

Safety: GS/TUV, CB, CE

Environmental: RoHS, WEEE

Weight: 158 grams

Dimension: 75 mm (L), 34 mm (W), 43 mm (H)

PART NUMBER	POWER RATING [W]	O/P VOLTAGE [V]	MAX. O/P CURRENT [A]	Additional
S-1298-0303	3.3	3.3	1.00	
S-1298-0312	3	12	0.25	
S-1298-0315	3	15	0.20	
S-1298-0503	5	3	1.50	
S-1298-0505	5	5	1.00	
S-1298-0509	5	9	0.55	
S-1298-0605	6	5	1.20	
S-1298-0606	6	6	1.00	
S-1298-0609	6	9	0.67	
S-1298-0610	6	10	0.60	
S-1298-0612	6	12	0.50	
S-1298-0615	6	15	0.40	
S-1298-0805	8	5	1.60	
S-1298-0806	8	6	1.33	
S-1298-0808	8	8	1.00	
S-1298-0815	8	15	0.50	
S-1298-0903	9	3	3.00	
S-1298-0906	9	6	1.50	
S-1298-0909	9	9	1.00	
S-1298-0918	9	18	0.50	
S-1298-1005	10	5	2.00	
S-1298-1010	10	10	1.00	
S-1298-1012	10	12	0.80	
S-1298-1015	10	15	0.63	

S-1298-1206	12	6	2.00	
S-1298-1209	12	9	1.33	
S-1298-1212	12	12	1.00	
S-1298-1305	13	5	2.60	
S-1298-1505	15	5	3.00	
S-1298-1506	15	6	2.50	
S-1298-1509	15	9	1.70	
S-1298-1512	15	12	1.25	
S-1298-1515	15	15	1.00	
S-1298-1518	15	18	0.85	
S-1298-1812	18	12	1.50	
S-1298-1815	18	15	1.20	
S-1298-1818	18	18	1.00	
S-1298-1824	18	24	0.75	
S-1298-2412H	24	12	2.00	

Product Code Rule

S	1298	24	12	W	2	E	1
S: switching L: linear D: DC/DC	Series	Watts	Output voltage	W: wall mount T: desktop B: open frame	Pin 2: 2 pins 3: 3 pins	E: European plug U: English plug -: USA plug	1: DC jack 5.5x2.1mm 2: DC jack 5.5x2.5mm 3: DC jack 3.5x1.35mm Other: call



S-1183

Input Voltage Type: Universal Range
 AC Input Voltage: 90~264 Vac
 AC Input Frequency: 47~63 Hz
 AC Input Current: 2A RMS Max.
 No. of Outputs: Single O/P
 O/P mode: Constant Voltage,
 Constant Current
 Load Regulation: +/-5%
 Min. O/P Amper: 0A
 Operation Temperature: 0-40°C
 Protection: Short, Over Voltage,
 Over Current
 MTBF: 35 000 Hours
 Hold Up Time: 10 ms
 Safety: cUL, TUV-PS/GS, CB, CE,
 Environmental: RoHS, WEEE
 Weight: 330 grams
 Dimension: 114 mm (L), 53.3 mm
 (W), 34 mm (H)

PART NUMBER	POWER RATING [W]	O/P VOLTAGE [V]	MAX. O/P CURRENT [A]	Additional
S-1183-3012	30	12	2.50	
S-1183-3013	30	13	2.31	
S-1183-3018	30	18	1.67	
S-1183-4005	40	5	8.00	
S-1183-4012	40	12	3.33	
S-1183-4015	40	15	2.67	
S-1183-4016	40	16	2.50	
S-1183-4018	40	18	2.22	
S-1183-4019	40	19	2.11	
S-1183-4020	40	20	2.00	
S-1183-4024	40	24	1.66	
S-1183-4212	42	12	3.50	
S-1183-4512	45	12	3.75	
S-1183-4513	45	13	3.46	
S-1183-4514	45	14	3.21	
S-1183-4515	45	15	3.00	
S-1183-4516	45	16	2.81	
S-1183-4518	45	18	2.50	
S-1183-4519	45	19	2.37	
S-1183-4520	45	20	2.25	
S-1183-4524	45	24	1.88	
S-1183-5012	50	12	4.17	

S-1183-5015	50	15	3.33	
S-1183-5016	50	16	3.13	
S-1183-5018	50	18	2.77	
S-1183-5019	50	19	2.63	
S-1183-5020	50	20	2.50	
S-1183-5024	50	24	2.08	
S-1183-6012	60	12	5.00	
S-1183-6015	60	15	4.00	
S-1183-6016	60	16	3.75	
S-1183-6518	60	18	3.33	
S-1183-6019	60	19	3.15	
S-1183-6020	60	20	3.00	
S-1183-6024	60	24	2.50	
S-1183-6512	65	12	5.41	
S-1183-6515	65	15	4.33	
S-1183-6516	65	16	4.06	
S-1183-6518	65	18	3.61	
S-1183-6519	65	19	3.42	
S-1183-6520	65	20	3.25	
S-1183-6524	65	24	2,70	

Product Code Rule

S	1183	65	24	W	2	E	1
S: switching L: linear D: DC/DC	Series	Watts	Output voltage	W: wall mount T: desktop B: open frame	Pin 2: 2 pins 3: 3 pins	E: European plug U: English plug -: USA plug	1: DC jack 5.5x2.1mm 2: DC jack 5.5x2.5mm 3: DC jack 3.5x1.35mm Other: call



S-1319

Input Voltage Type: Universal Range
 AC Input Voltage: 90~264 Vac
 AC Input Frequency: 47~63 Hz
 AC Input Current: 1.6A RMS
 O/P mode: Constant Voltage
 No. of Outputs: Single O/P
 Load Regulation: +/-5%
 Min. O/P Amper: 0A
 Operation Temperature: 0~40°C
 Protection: Short, Over Voltage, Over Current
 MTBF: 35 000 Hours
 Hold Up Time: 10 ms
 Safety: cUL, TUV, CB, CE
 Environmental: RoHS, WEEE
 Weight: 200 grams
 Dimension: 86.5 mm (L), 47.4 mm (W), 32.0 mm (H)

PART NUMBER	POWER RATING [W]	O/P VOLTAGE [V]	MAX. O/P CURRENT [A]	Additional Safety
S-1319-0505	5	5	1.00	
S-1319-0509	5	9	0.55	
S-1319-0605	6	5	1.20	
S-1319-0606	6	6	1.00	
S-1319-0609	6	9	0.66	
S-1319-0612	6	12	0.50	
S-1319-0705	7	5	1.40	
S-1319-0706	7	6	1.16	
S-1319-0709	7	9	0.77	
S-1319-0712	7	12	0.58	
S-1319-0805	8	5	1.60	
S-1319-0806	8	6	1.33	
S-1319-0809	8	9	0.88	
S-1319-0812	8	12	0.66	
S-1319-0815	8	15	0.53	
S-1319-0816	8	16	0.50	
S-1319-0905	9	5	1.80	
S-1319-0906	9	6	1.50	
S-1319-0909	9	9	1.00	
S-1319-0912	9	12	0.75	
S-1319-0915	9	15	0.60	
S-1319-0916	9	16	0.56	

S-1319-0918	9	18	0.50	
S-1319-1005	10	5	2.00	
S-1319-1006	10	6	1.66	
S-1319-1009	10	9	1.11	
S-1319-1012	10	12	0.83	
S-1319-1015	10	15	0.66	
S-1319-1016	10	16	0.62	
S-1319-1018	10	18	0.55	
S-1319-1019	10	19	0.52	
S-1319-1020	10	20	0.50	
S-1319-1105	11	5	2.20	
S-1319-1106	11	6	1.83	
S-1319-1109	11	9	1.22	
S-1319-1112	11	12	0.91	
S-1319-1115	11	15	0.73	
S-1319-1116	11	16	0.68	
S-1319-1118	11	18	0.61	
S-1319-1119	11	19	0.57	
S-1319-1120	11	20	0.55	
S-1319-1205	12	5	2.40	
S-1319-1206	12	6	2.00	
S-1319-1209	12	9	1.33	
S-1319-1212	12	12	1.00	
S-1319-1215	12	15	0.80	
S-1319-1216	12	16	0.75	
S-1319-1218	12	18	0.66	
S-1319-1219	12	19	0.63	
S-1319-1220	12	20	0.60	
S-1319-1224	12	24	0.50	
S-1319-1305	13	5	2.60	
S-1319-1306	13	6	2.16	
S-1319-1309	13	9	1.44	
S-1319-1312	13	12	1.08	
S-1319-1315	13	15	0.86	
S-1319-1316	13	16	0.81	
S-1319-1318	13	18	0.72	
S-1319-1319	13	19	0.68	
S-1319-1320	13	20	0.65	
S-1319-1324	13	24	0.54	
S-1319-1405	14	5	2.80	
S-1319-1406	14	6	2.33	
S-1319-1409	14	9	1.55	
S-1319-1412	14	12	1.16	
S-1319-1415	14	15	0.93	
S-1319-1416	14	16	0.87	
S-1319-1418	14	18	0.77	
S-1319-1419	14	19	0.73	
S-1319-1420	14	20	0.70	

S-1319-1424	14	24	0.58	
S-1319-1505	15	5	3.00	
S-1319-1506	15	6	2.16	
S-1319-1509	15	9	1.66	
S-1319-1512	15	12	1.25	
S-1319-1515	15	15	1.00	
S-1319-1516	15	16	0.93	
S-1319-1518	15	18	0.83	
S-1319-1519	15	19	0.78	
S-1319-1520	15	20	0.75	
S-1319-1524	15	24	0.62	
S-1319-1605	16	5	3.20	
S-1319-1606	16	6	2.66	
S-1319-1609	16	9	1.77	
S-1319-1612	16	12	1.33	
S-1319-1615	16	15	1.06	
S-1319-1616	16	16	1.00	
S-1319-1618	16	18	0.88	
S-1319-1619	16	19	0.84	
S-1319-1620	16	20	0.80	
S-1319-1624	16	24	0.66	
S-1319-1705	17	05	3.40	
S-1319-1706	17	06	2.83	
S-1319-1709	17	09	1.88	
S-1319-1712	17	12	1.41	
S-1319-1715	17	15	1.13	
S-1319-1716	17	16	1.06	
S-1319-1718	17	18	0.94	
S-1319-1719	17	19	0.89	
S-1319-1720	17	20	0.85	
S-1319-1724	17	24	0.70	
S-1319-1805	18	5	3.60	
S-1319-1806	18	6	3.00	
S-1319-1809	18	9	2.00	
S-1319-1812	18	12	1.50	
S-1319-1815	18	15	1.20	
S-1319-1816	18	16	1.12	
S-1319-1818	18	18	1.00	
S-1319-1819	18	19	0.94	
S-1319-1820	18	20	0.90	
S-1319-1824	18	24	0.75	
S-1319-1905	18	5	3.60	
S-1319-1906	19	6	3.16	
S-1319-1912	19	12	1.58	
S-1319-1915	19	15	1.26	
S-1319-1916	19	16	1.18	
S-1319-1918	19	18	1.05	
S-1319-1919	19	19	1.00	

S-1319-1920	19	20	0.95	
S-1319-1924	19	24	0.79	
S-1319-2006	20	6	3.33	
S-1319-2009	20	9	2.22	
S-1319-2012	20	12	1.66	
S-1319-2015	20	15	1.33	
S-1319-2016	20	16	1.25	
S-1319-2018	20	18	1.11	
S-1319-2019	20	19	1.05	
S-1319-2020	20	20	1.00	
S-1319-2024	20	24	0.83	
S-1319-2106	21	6	3.50	
S-1319-2109	21	9	2.33	
S-1319-2112	21	12	1.75	
S-1319-2115	21	15	1.40	
S-1319-2118	21	18	1.16	
S-1319-2119	21	19	1.10	
S-1319-2120	21	20	1.05	
S-1319-2124	21	24	0.87	
S-1319-2206	22	6	3.66	
S-1319-2209	22	9	2.44	
S-1319-2212	22	12	1.83	
S-1319-2215	22	15	1.46	
S-1319-2216	22	16	1.37	
S-1319-2218	22	18	1.22	
S-1319-2219	22	19	1.15	
S-1319-2220	22	20	1.10	
S-1319-2224	22	24	0.91	
S-1319-2306	23	6	3.83	
S-1319-2309	23	9	2.55	
S-1319-2312	23	12	1.91	
S-1319-2315	23	15	1.53	
S-1319-2316	23	16	1.43	
S-1319-2318	23	18	1.27	
S-1319-2319	23	19	1.21	
S-1319-2320	23	20	1.15	
S-1319-2324	23	24	0.95	
S-1319-2406	24	6	4.00	
S-1319-2409	24	9	2.66	
S-1319-2412	24	12	2.00	
S-1319-2415	24	15	1.60	
S-1319-2416	24	16	1.50	
S-1319-2418	24	18	1.33	
S-1319-2419	24	19	1.26	
S-1319-2420	24	20	1.20	
S-1319-2424	24	24	1.00	
S-1319-2506	25	6	4.16	
S-1319-2509	25	9	2.77	

S-1319-2512	25	12	2.08	
S-1319-2515	25	15	1.66	
S-1319-2516	25	16	1.56	
S-1319-2518	25	18	1.38	
S-1319-2519	25	19	1.31	
S-1319-2520	25	20	1.25	
S-1319-2524	25	24	1.04	
S-1319-2609	26	9	2.88	
S-1319-2612	26	12	2.16	
S-1319-2615	26	15	1.73	
S-1319-2616	26	16	1.62	
S-1319-2618	26	18	1.44	
S-1319-2619	26	19	1.36	
S-1319-2620	26	20	1.30	
S-1319-2624	26	24	1.08	
S-1319-2709	27	9	3.00	
S-1319-2712	27	12	2.25	
S-1319-2715	27	15	1.80	
S-1319-2716	27	16	1.68	
S-1319-2718	27	18	1.50	
S-1319-2719	27	19	1.42	
S-1319-2720	27	20	1.35	
S-1319-2724	27	24	1.12	
S-1319-2812	28	12	2.33	
S-1319-2815	28	15	1.86	
S-1319-2816	28	16	1.75	
S-1319-2818	28	18	1.55	
S-1319-2819	28	19	1.47	
S-1319-2820	28	20	1.40	
S-1319-2824	28	24	1.16	
S-1319-2912	29	12	2.41	
S-1319-2915	29	15	1.93	
S-1319-2916	29	16	1.81	
S-1319-2918	29	18	1.61	
S-1319-2919	29	19	1.52	
S-1319-2920	29	20	1.45	
S-1319-2924	29	24	1.20	
S-1319-3012	30	12	2.50	
S-1319-3015	30	15	2.00	
S-1319-3016	30	16	1.87	
S-1319-3018	30	18	1.66	
S-1319-3019	30	19	1.57	
S-1319-3020	30	20	1.50	
S-1319-3024	30	24	1.25	

Product Code Rule

S	1319	30	24	W	2	E	1
S: switching L: linear D: DC/DC	Series	Watts	Output voltage	W: wall mount T: desktop B: open frame	Pin 2: 2 pins 3: 3 pins	E: European plug U: English plug -: USA plug	1: DC jack 5.5x2.1mm 2: DC jack 5.5x2.5mm 3: DC jack 3.5x1.35mm

Jade-Technologie
14, square de la Poterne
91300 MASSY - France
Tel. 33 1 60 11 61 59
Fax. 33 1 60 13 37 52

Room 1002, 10/F, Honest Motors Building
9-11 Leighton Road, Causeway Bay
Hong -Kong



S-1318

Input Voltage Type: Universal Range

AC Input Voltage: 90~264 Vac

AC Input Frequency: 47~63 Hz

AC Input Current: 1.6A RMS

No. of Outputs: Single O/P

O/P mode: Constant Voltage

Load Regulation: +/-5%

Min. O/P Amper: 0A

Operation Temperature: 0~32°C

Protection: Short, Over Voltage, Over Current

MTBF: 35 000 Hours

Hold Up Time: 10 ms

Safety: cUL, TUV/GS, CB, CE

Environmental: RoHS, WEEE

Weight: 300 grams

Dimension: 100 mm (L), 45.0 mm (W), 30.0 mm (H)

PART NUMBER	POWER RATING [W]	O/P VOLTAGE [V]	MAX. O/P CURRENT [A]	Additional
S-1318-4016	40	16	2.50	
S-1318-4019	40	19	2.10	
S-1318-4020	40	20	2.00	
S-1318-4024	40	24	1.66	
S-1318-4116	41	16	2.56	
S-1318-4119	41	19	2.15	
S-1318-4120	41	20	2.05	
S-1318-4124	41	24	1.70	
S-1318-4216	42	16	2.62	
S-1318-4219	42	19	2.21	
S-1318-4220	42	20	2.10	
S-1318-4224	42	24	1.75	
S-1318-4316	43	16	2.68	
S-1318-4319	43	19	2.26	
S-1318-4320	43	20	2.15	
S-1318-4324	43	24	1.79	
S-1318-4416	44	16	2.75	
S-1318-4419	44	19	2.31	
S-1318-4420	44	20	2.20	
S-1318-4424	44	24	1.83	
S-1318-4516	45	16	2.81	
S-1318-4519	45	19	2.36	

S-1318-4520	45	20	2.25	
S-1318-4524	45	24	1.87	
S-1318-4616	46	16	2.87	
S-1318-4619	46	19	2.42	
S-1318-4620	46	20	2.30	
S-1318-4624	46	24	1.91	
S-1318-4716	47	16	2.93	
S-1318-4719	47	19	2.47	
S-1318-4720	47	20	2.35	
S-1318-4724	47	24	1.95	
S-1318-4816	48	16	3.00	
S-1318-4819	48	19	2.52	
S-1318-4820	48	20	2.40	
S-1318-4824	48	24	2.00	
S-1318-4916	49	16	3.06	
S-1318-4919	49	19	2.57	
S-1318-4920	49	20	2.45	
S-1318-4924	49	24	2.04	
S-1318-5016	50	16	3.12	
S-1318-5019	50	19	2.63	
S-1318-5020	50	20	2.50	
S-1318-5024	50	24	2.08	
S-1318-5116	51	16	3.18	
S-1318-5119	51	19	2.68	
S-1318-5120	51	20	2.55	
S-1318-5124	51	24	2.12	
S-1318-5216	52	16		
S-1318-5219	52	19	2.73	
S-1318-5220	52	20	2.60	
S-1318-5224	52	24	2.08	
S-1318-5316	53	16	3.31	
S-1318-5319	53	19	2.78	
S-1318-5320	53	20	2.65	
S-1318-5324	53	24	2.20	
S-1318-5416	54	16	3.37	
S-1318-5419	54	19	2.84	
S-1318-5420	54	20	2.70	
S-1318-5424	54	24	2.25	
S-1318-5516	55	16	3.43	
S-1318-5519	55	19	2.89	
S-1318-5520	55	20	2.75	
S-1318-5524	55	24	2.29	
S-1318-5616	56	16	3.50	
S-1318-5619	56	19	2.94	
S-1318-5620	56	20	2.80	
S-1318-5624	56	24	2.33	
S-1318-5716	57	16	3.56	
S-1318-5719	57	19	3.00	

S-1318-5720	57	20	2.85	
S-1318-5724	57	24	2.37	
S-1318-5816	58	16	3.62	
S-1318-5819	58	19	3.05	
S-1318-5820	58	20	2.90	
S-1318-5824	58	24	2.41	
S-1318-5916	59	16	3.68	
S-1318-5919	59	19	3.10	
S-1318-5920	59	29	2.03	
S-1318-5924	59	24	2.45	
S-1318-6016	60	16	3.75	
S-1318-6019	60	19	3.15	
S-1318-6020	60	20	3.00	
S-1318-6024	60	24	2.50	

Product Code Rule

S	1318	60	24	W	2	E	1
S: switching L: linear D: DC/DC	Series	Watts	Output voltage	W: wall mount T: desktop B: open frame	Pin 2: 2 pins 3: 3 pins	E: European plug U: English plug -: USA plug	1: DC jack 5.5x2.1mm 2: DC jack 5.5x2.5mm 3: DC jack 3.5x1.35mm Other: call



S-1223

Input Voltage Type: Universal Range
 AC Input Voltage: 90~264 Vac
 AC Input Frequency: 47~63 Hz
 AC Input Current: 3A RMS
 Power Factor: 0.9 Minimum
 No. of Outputs: Single Output
 O/P mode: Constant Voltage, Constant Current
 Load Regulation: +/-5%
 Min. O/P Amper: 0A
 Operation Temperature: 0~40°C
 Protection: Short, Over Voltage, Over Current
 MTBF: 35 000 hours
 Hold Up Time: 10 ms
 Safety: cUL, TUV-PS/GS, CE, CB,
 Environmental: RoHS, WEEE
 Weight: 410 grams
 Dimension: 138.5 mm (L), 61 mm (W),
 32.5 mm (H)

PART NUMBER	POWER RATING [W]	O/P VOLTAGE [V]	MAX. O/P CURRENT [A]	Additional
S-1223-7512	75	12	6.25	
S-1223-7515	75	15	5.00	
S-1223-7516	75	16	4.70	
S-1223-7518	75	18	4.16	
S-1223-7519	75	19	3.94	
S-1223-7522	75	22	3.41	
S-1223-7524	75	24	3.12	
S-1223-8012	80	12	6.66	
S-1223-8515	85	15	5.66	
S-1223-8517	85	17	5.00	
S-1223-9019	90	19	4.73	
S-1223-9020	90	20	4.50	
S-1223-9024	90	24	3.75	

Product Code Rule

S	1223	90	24	W	2	E	1
S: switching L: linear D: DC/DC	Series	Watts	Output voltage	W: wall mount T: desktop B: open frame	Pin 2: 2 pins 3: 3 pins	E: European plug U: English plug -: USA plug	1: DC jack 5.5x2.1mm 2: DC jack 5.5x2.5mm 3: DC jack 3.5x1.35mm Other: call



S-1250

Input Voltage Type: Universal Range
 AC Input Voltage: 90~264 Vac
 AC Input Frequency: 47~63 Hz
 AC Input Current: 3A RMS
 Power Factor: 0.9 Minimum
 No. of Outputs: Single Output
 O/P mode: Constant Voltage, Constant Current
 Load Regulation: +/-5%
 Min. O/P Amper: 0A
 Operation Temperature: 0~40°C
 Protection: Short, Over Voltage, Over Current
 MTBF: 35 000 hours
 Hold Up Time: 10 ms
 Safety: cUL, TUV-PS/GS, CE, CB,
 Environmental: RoHS, WEEE
 Weight: 525 grams
 Dimension: 168.3 mm (L), 60 mm (W), 38.1 mm (H)

PART NUMBER	POWER RATING [W]	O/P VOLTAGE [V]	MAX. O/P CURRENT [A]	Additional
S-1250-A212	120	12	10.0	
S-1250-A215	120	15	8.00	
S-1250-A220	120	20	6.00	
S-1250-A319	130	19	6.84	
S-1250-A324	130	24	5.41	

Product Code Rule

S	1250	A3	24	W	2	E	1
S: switching L: linear D: DC/DC	Series	Watts A2: 120 A3: 130	Output voltage	W: wall mount T: desktop B: open frame	Pin 2: 2 pins 3: 3 pins	E: European plug U: English plug -: USA plug	1: DC jack 5.5x2.1mm 2: DC jack 5.5x2.5mm 3: DC jack 3.5x1.35mm Other: call